

SPRAY GUN NOZZLE RECOMMENDATIONS



National Rule Products		LPH300	W400LV	LPH400LV	LPH400LVX	SUPERNOVA LS400 ENTECH	SUPERNOVA WS400 EVO
Primers							
1K Etching Primer	Nozzle Size	1.3-1.4 mm					
	Air Pressure	18 psi					
Primer Surfacer							
HS Surfacer	Nozzle Size	1.4-1.6 mm					
	Air Pressure	18 psi					
Urethane Surfacer	Nozzle Size	1.4-1.6 mm					
	Air Pressure	18 psi					
Primer Sealer							
Lesonal HS Sealer	Nozzle Size	1.3-1.4 mm					
	Air Pressure	18 psi					
Low VOC Primer							
LV HS Surfacer	Nozzle Size	1.4-1.6 mm					
	Air Pressure	18 psi					
LV HS Sealer	Nozzle Size	1.3-1.4 mm					
	Air Pressure	18 psi					
Basecoat							
Basecoat SB	Nozzle Size		1.3-1.4 mm	1.3-1.4 mm	1.3-1.4 mm		
	Air Pressure		16 psi	16 psi	16 psi	26 psi	
Waterborne Basecoat							
Basecoat WB	Nozzle Size		1.3-1.4 mm	1.3-1.4 mm	1.3-1.4 mm		
	Air Pressure		16 psi	16 psi	16 psi	26 psi	
Clearcoat							
Glamor Clear	Nozzle Size		1.3-1.4 mm	1.3-1.4 mm			1.3-1.5 mm
	Air Pressure		20 psi	16 psi			29 psi
ProAir Clear	Nozzle Size		1.3-1.4 mm	1.3-1.4 mm			1.3-1.5 mm
	Air Pressure		20 psi	16 psi			29 psi
Universal Clearcoat	Nozzle Size		1.3-1.4 mm	1.3-1.4 mm			1.3-1.5 mm
	Air Pressure		20 psi	16 psi			29 psi
LV Clear	Nozzle Size		1.3-1.4 mm	1.3-1.4 mm			1.3-1.5 mm
	Air Pressure		20 psi	16 psi			29 psi
ProAir LV	Nozzle Size		1.3-1.4 mm	1.3-1.4 mm			1.3-1.5 mm
	Air Pressure		20 psi	16 psi			29 psi

These recommendations are based on reliable research.

Experimentation may be required with multiple fluid nozzle recommendations, to best suit your application technique.

Referenced air pressure data in this chart are all measured with full trigger.

The recommended air pressure must be set with a full trigger condition on the spray gun.

All trademarks are the property of their respective owners.

© 2018 ANEST IWATA USA, Inc.