



SPRAY GUN NOZZLE RECOMMENDATIONS



Smart Look. Smart Choice.



National Rule Products		LPH300	W400LV	LPH400LV	LPH400LVX	SUPERNOVA LS400 ENTECH	SUPERNOVA WS400 EVO
Primers							
Wanda 8100 2K Primer	Nozzle Size	2.0 mm					
	Air Pressure	18 psi					
Primer Surfacer							
Wanda 8100 2K Primer	Nozzle Size	1.6 mm					
	Air Pressure	18 psi					
Primer Sealer							
Wanda Non Sand Sealer	Nozzle Size	1.6 mm					
	Air Pressure	18 psi					
Wanda Plastic Primer	Nozzle Size	1.4 mm					
	Air Pressure	18 psi					
Low VOC Primer							
Wanda Low VOC Primer	Nozzle Size	1.6 mm					
	Air Pressure	18 psi					
Low VOC Sealer							
Wanda Low VOC Sealer	Nozzle Size	1.6 mm					
	Air Pressure	18 psi					
Single Stage							
Wanda PU	Nozzle Size			1.4 mm	1.4 mm	1.4 mm	
	Air Pressure			16 psi	16 psi	26 psi	
Basecoat							
Wandabase HS	Nozzle Size			1.4 mm	1.4 mm	1.4 mm	
	Air Pressure			16 psi	16 psi	26 psi	
Waterborne Basecoat							
Wanda Waterbase	Nozzle Size		1.4 mm	1.4 mm	1.4 mm	1.4 mm	1.4 mm
	Air Pressure		20 psi	16 psi	16 psi	26 psi	29 psi
Clearcoat							
Wanda 8100 Clearcoat	Nozzle Size		1.4 mm	1.4 mm		1.4 mm	1.4 mm
	Air Pressure		20 psi	16 psi		26 psi	29 psi
Wanda Low VOC Clearcoat	Nozzle Size		1.4 mm	1.4 mm		1.4 mm	1.4 mm
	Air Pressure		20 psi	16 psi		26 psi	29 psi

These recommendations are based on reliable research.
Experimentation may be required with multiple fluid nozzle recommendations, to best suit your application technique.
Referenced air pressure data in this chart are all measured with full trigger.
The recommended air pressure must be set with a full trigger condition on the spray gun.

All trademarks are the property of their respective owners.
© 2018 ANEST IWATA USA, Inc.