

# PT / PET-MN SERIES

## PRESSURE POTS



PT Series



***Consistent agitation.  
Consistent quality.***

Manual and automatic agitated pressure pots

### PT Series Pressure Pots

- Available in sizes ranging from 10L to 80L
- Available in pneumatic agitated and manual configurations
- Precision machined tank closure system allows for easy access

### PET Series Pressure Pots

- Stainless steel vessel with polished interior & SST pickup tube
- Available in sizes from 10L to 50L in both agitated and non-agitated configurations
- Quiet and efficient three-piston agitators on MN models
- Dual regulation optional

PET Series



See reverse for ordering information



# ORDERING INFO



## ORDER Information - PT-10D | PT-20D | PT-40D | PT-60D | PT-80D - MANUAL AGITATION

Code	Model	Capacity (GAL)	Max Pressure (bar/psi)	Approx Dimensions HxLxW (in)	Weight (lbs)	safety valve	Air Regulator	Temp Range
6301B	PT-10D	2.6	3.4 / 49.3	21.5 x 14.6 x 12.4	28	SVB-8-35	RR-56B	41~104°F
6303B	PT-20D	5.2		25.7 x 15.4 x 13	43			
6304	PT-40D	10.5	1.8 / 26.1	27.6 x 18.3 x 18.1	59.5	SVB-8-19		
6316	PT-60D	15.9		34.8 x 18.3 x 19.7	77.1			
6318	PT-80D	21.1		41.1 x 18.3 x 19.7	84.9			

Air inlet & Outlet Fitting: G1/4"  
 PT10D & PT20D: Fluid Outlet Fitting: G3/8" x 1  
 PT-40D & PT-60D & PT-80D: Fluid Outlet Fitting: G3/8" x 2

## ORDER Information - PT-10DM | PT-20DM | PT-40DM | PT-60DM | PT-80DM - AUTOMATIC AGITATION

Code	Model	Capacity (GAL)	Max Pressure (bar/psi)	Approx Dimensions HxLxW (in)	Weight (lbs)	safety valve	Air Regulator	Temp Range
6302B	PT-10DM	2.6	3.4 / 49.3	19x 14.6 x 12.4	29.8	SVB-8-35	RR-56B	41~104°F
6300B	PT-20DM	5.2		23.2 x 15.4 x 13	50.7			
6305B	PT-40DM	10.5	1.8 / 26.1	25.5 x 18.3 x 18.1	67.2	SVB-8-19		
6317	PT-60DM	15.9		32.6 x 18.3 x 19.7	82.7			
6319	PT-80DM	21.1		39.4 x 18.3 x 19.7	92.6			

Air inlet & Outlet Fitting: G1/4"  
 PT10DM & PT20DM: Fluid Outlet Fitting: G3/8" x 1  
 PT-40DM & PT-60DM & PT-80DM: Fluid Outlet Fitting: G3/8" x 2

## ORDER Information - PET-10N/MN | PET-30N/MN | PET-50N/MN

Code	Model	Capacity (L)	Max Pressure (bar/psi)	Approx Dimensions HxLxW (in)	Weight (lbs)	Air Inlet Joint	Fluid Outlet Joint	Working Temp
6340	PET-10N	10	7 bar (100 psi)	21.3 x 13	33.7	G 1/4" M	G 3/8" M	5~40° C 41~104° F
6341	PET-10MN WITH PNEUMATIC AGITATOR				38.6			
6335	PET-30N	30		28 x 16.3	45			
6336	PET-30MN WITH PNEUMATIC AGITATOR				49.8			
6342	PET-50N	50		31.9 x 18.5	33.7			
6343	PET-50MN WITH PNEUMATIC AGITATOR				62.2			